

## **MATERIAL SAFETY DATA SHEET**

NOTE: BLANK SPACES ARE NOT I	PERMITTED	. IF ANY ITEM	M IS NOT APPLICABI	LE, TH	E SPACE MUS	T BE MARKED	TO INDICATE THAT.	
IDENTITY					PART NO.			
(As shown on Label or package) INSUL-COAT F-910					IF APPLICABLE: 29980217			
SECTION I								
MANUFACTURER'S				EMERGENCY PHONE No.				
NAME Formulated Speci	fically for Bro	nz-Glow		USA only: 1-800-424-9300 INT'L: 703-527-3887				
ADDRESS (NUMBER, STREET, CITY				REVISION # 0001				
175 Bronz-Glow Way	,	ŕ						
				MANUFACTURER'S PHONE				
St. Augustine, FL 32095				<b>No. FOR INFORMATION</b> 904-825-0175				
				DATE MSDS				
				WAS PREPARED March 10, 2005				
SECTION II - HAZARDOUS INGREI	DIENTS INFO	RMATION. A	all Health Hazards which	ch comp	rise 1% or gre	ater of the comp	osition and all	
carcinogens if 0.1% of the composition	or greater.							
HAZARDOUS COMPONENTS CHE	MICAL and	% Wt.	% Wt. CAS NO.		OSHA	ACGIH	OTHER LIMITS	
IDENTITY AND COMMON NA	ME (S)	(OPTIONA)	L)		PEL	TLV	RECOMMEND	
Acetone		29 - 37	67-64-1		1000 ppm	500 ppm	None	
Toluene		20 - 26	108-88-3		200 ppm	50 ppm	None	
Methyl Ethyl Ketone		8 - 13	78-93-3		200 ppm	200 ppm	None	
Xylene		5 - 10	1330-20-7		100 ppm	100 ppm	None	
Ethylbenzene		1 - 3	100-41-4		100 ppm	100 ppm	None	
SECTION III - PHYSICAL / CHEMIC	CAL CHARA	CTERISTICS						
BOILING	SPECIFIC	GRAVITY (H <sub>2</sub> 0	0=1)	APPROXIMATE WEIGHT PER GALLON (LBS)				
<b>POINT</b> 133 - 279°F	0.89 - 0.91			7.45 – 7.58				
VAPOR PRESSURE	VAPOR DE	ENSITY			EVAPORATION RATE			
185 mmHg @ 20°C	(AIR = 1) Heavier than air				(BUTYL ACETATE =1) $> 1.0$			
SOLUBILITY IN WATER	% VOLATILE 34 – 52%				OTHER			
Slight	<b>VOC LBS./GAL</b> 2.5 – 3.9				(IF ANY) None			
APPEARANCE								
AND ODOR Characteristic solvent								
SECTION IV-FIRE AND EXPLOSION	N HAZARD D	ATA						
FLASH POINT - 4.0°F F			FLAMMABLE LIMIT	ΓS	LEL		UEL	
(METHOD USED) TCC					1.0		12.8	
EXTINGUISHING								
MEDIA Carbon Dioxide, Dry	Chemical, or I	Foam						
SPECIAL FIRE								
	ontained breatl	ning apparatus w	vith a full face piece, ope	erated in	pressure deman	d or other positive	e pressure mode.	
UNUSUAL FIRE AND				CI.		•.		
EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.								
HAZARDOUS PRODUCTS FORMED BY  FIRE OR THERMAL DECOMPOSITION Codes Dissidered (a Codes Managida Hadrons Providered Chlorida and Alberta and								
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide. Hydrogen Bromide and Chloride, and other organic hydrocarbons.  EXPLOSIVE LIMITS								
(% BY VOLUME IN AIR) 1.0 – 12.8								
SECTION V - OPTIONAL HAZARD	DATINGS ID	ENTIFICATIO	NY.					
HAZARD RATING	XATINGS ID	ENTIFICATIO		4 4	A i - 4i (N	EDA		
4-EXTREME			Nauonai Fire Pr	National Fire Protection Association (NFPA)				
3-HIGH			FIRE 3 F	FIRE 3 REACTIVITY 0.				
2-MODERATE								
1-SLIGHT								
					2 SPECIAL HAZARDS None .			
**SEE SECTION IV								

SECTION VI - REACTIVITY AND STABILITY DATA								
STABILITY UNSTABLE STABLE X CONDITIONS TO AVOID Temperatures over 350°F for over 10 minutes.								
INCOMPATIBILITY Oxidizing M	Iaterials	*						
HAZARDOUS DECOMPOSITIO	N OR BY PRODUCTS Carbon Monoxide, C	Carbon Dioxide, Hydrogen Chloride	e, and other organic hydrocarbons.					
HAZARDOUS	MAY OCCUR	CONDITIONS TO AVOID	-					
POLYMERIZATION	WILL NOT OCCUR X	None						
SECTION VII - HEALTH HAZA	RD DATA							
ROUTES OF ENTRY	INHALATION? Yes SKIN? Yes	INGESTION? Yes	EYES? Yes					
HEALTH ACUTE	X   See Signs and Symptoms of Exposure	e below.						
HAZARDS CHRONIC	X							
CARCINOGENICITY: IARC 2B								
SIGNS AND								
SYMPTOMS OF	Inhalation: Headache, nausea, and irritation	of nose, throat and lungs. Skin: I	rritation upon repeat or					
EXPOSURE	prolonged contact. Eyes: Slightly irritation	to eyes.						
MEDICAL CONDITIONS GENE	RALLY AGGRAVATED BY EXPOSURE	None known						
EMERGENCY AND	T. C. (Pl.:: P. C.	. 17 . 17 . 1						
EMERGENCY AND FIRST AID		Ingestion: Contact Physician or Poison Control Immediately.  Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary.						
PROCEDURES	Eye Contact: Flush with large amounts of w							
PROCEDURES	Skin: Wash with soap and water.	vater. Il irritation persists, contact l	Physician.					
SECTION VIII DDECAUTIONS	FOR SAFE HANDLING AND USE							
SECTION VIII - PRECAUTIONS	FOR SAFE HANDLING AND USE							
CTEDS TO DE TAKEN	Windowski floor look Tour fort l							
STEPS TO BE TAKEN		bsorbent. Transfer to hood. Prevent run-off to sewers.  of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material						
IN CASE MATERIAL IS RELEASED OR SPILLED								
RELEASED OR SPILLED	to dam or contain spills. If large spill, notify	y appropriate state and local agenci	es.					
WASTE DISPOSAL METHODS	Dispose of product in accordance with local, c	ounty state and federal regulations	,					
WASTE DISTOSAL METHODS	Dispose of product in accordance with local, c	county, state and rederar regulations	). 					
PRECAUTIONS TO BE	Keep away from sparks, flame and heat sour	rces Store in cool ventilated area						
TAKEN IN HANDLING								
AND STORAGE	Avoid contact with eyes. Keep container closed. Use with adequate ventilation. Avoid inhalation of vapors and personal contact with liquid product. Use good personal hygiene practices.							
1112 51 511152		g f	·					
OTHER	Keep container closed when not in use. All	containers should be disposed in a	n environmentally safe manner					
PRECAUTIONS	accordance with governmental regulations.		, , , , , , , , , , , , , , , , , , ,					
SECTION IX - CONTROL MEASURES								
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne concentration, use a Respirator  PROTECTIVE GLOVES								
or Gas Mask with appropriate NIOSH approved cartridge and cannister, or supplied air equipment.  Impervious gloves								
	EXHAUST Supplemental (if needed)		SPECIAL None					
MECHA	NICAL (GENERAL) To maintain exposure	below PEL's OTHER Chem	ical Apron/Eye bath/Safety shower					
EYE PROTECTION	, , , , , , , , , , , , , , , , , , ,		E CLOTHING OR EQUIPMENT					
Chemical splash goggles or approve	d eye protection.	None						
WORK HYGIENIC PRACTICES Wash thoroughly after handling.								
SECTION X - TRANSPORTATION INFORMATION (Optional)								
DOT PROPER SHIPPING NAME Coating Solution DOT HAZARD CLASS 3								
DOT UN NUMBER UN 1139		DOT PACKING GROUP II						
IATA PROPER SHIPPING NAM	E Coating Solution	IATA HAZARD CLASS 3						
IATA UN NUMBER UN 1139		IATA PACKING GROUP II						
SECTION XI - 313 SUPPLIER NOTIFICATION								
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight). Toluene, Methyl Ethyl Ketone, Xylene, and Ethylbenzene								
		IE STATE OF CALLEODNIA TO	CALISE CANCED AND DIDTH					
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.								

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Andrew	Stooksbury	