



Datos de Rendimiento de Semiherméticos Para Aire Acondicionado - **R-22 - 60 Hz - BTUH**

Modelo	Cond. Temp °F	45°F	35°F	25°F	20°F	15°F	10°F	0°F	-10°F
		7.2°C	1.7°C	-3.9°C	-6.7°C	-9.4°C	-12.2°C	-17.8°C	-23.3°C
<b>MODELOS ENFRIADOS POR REFRIGERANTE R-22</b>									
<b>NRA2-0500</b>	90	79,600	64,400	51,100	45,100	39,500			
	110	69,100	55,800	44,000	38,700	33,800			
	130	57,600	46,290	36,300	31,800	27,700			
<b>NRM1-0500</b>	90	95,300	77,100	61,200	54,500	48,500			
	110	83,200	67,200	53,000	47,100	41,700			
	130	71,100	57,100	44,800	39,600	34,900			
<b>MRH4-0760</b>	90	114,500	93,000	74,000	65,000	57,000			
	110	98,500	80,000	64,000	56,000	49,000			
	130	82,000	67,000	53,000	46,500	41,000			
<b>9RC1-1015</b>	90	156,000	128,000	105,000	95,000	85,000			
	110	138,000	113,000	92,000	82,000	72,000			
	130	120,000	98,000	78,000	69,500	61,500			
<b>9RS1-1505</b>	90	213,000	172,000	139,000	124,000	110,000			
	110	184,000	149,000	119,000	105,000	91,500			
	130	142,000	115,000	90,000	78,000	66,000			
<b>4RA3-2000</b>	90	261,000	215,000	169,000	153,000	140,000			
	110	232,000	191,000	149,000	132,000	116,000			
	130	200,000	164,000	128,000	113,000	98,800			
<b>4RH1-2500</b>	90	349,000	278,000	219,000	194,000	174,000			
	110	299,000	238,000	187,000	165,000	147,000			
	130	249,000	199,000	156,000	138,000	122,000			
<b>4RJ2-3000</b>	90	384,000	315,000	252,000	224,000	196,000			
	110	327,000	268,000	212,000	188,000	165,000			
	130	269,000	220,000	174,000	155,000	135,000			
<b>6RH1-3500</b>	90	482,000	385,000	303,000	268,000	239,000			
	110	415,000	338,000	271,000	241,000	215,000			
	130	357,000	293,000	235,000	209,000	186,000			
<b>6RJ1-4000</b>	90	520,000	420,000	340,000	290,000	258,000			
	110	455,000	365,000	280,000	255,000	222,000			
	130	387,000	310,000	240,000	212,000	185,000			