



HYPERWATT
Water Heating Chiller Pressurizer

**Higher 30kW Capacity Rapidly
 Pressurizes a Chiller**



Portable Service Cart Model

- Microprocessor displays step-by-step operating instructions.
- When desired chiller pressure level is reached, the pump shuts down. Automatically re-energizes to maintain stable pressure.
- Microprocessor monitors chiller pressure and prevents overpressurization.
- Thermal sensors prevent heating element overload and burnout.
- Sensor halts operations should water flow cease.
- 100-lb portable model easily managed by one man and maneuvered around tight mechanical rooms.
- Permanent mount unit is hard piped to a chiller. Maintains the chiller at slightly positive pressure during seasonal shutdown.

Specifications

Power: Controls & Water Pump	115/60/1 110/50/1
Dimensions - Inches: l x w x h	20 x 22 x 51
Weight	100-lbs
Pressure settings	0 to 10-psi

Included with purchase

- 100-ft power cord for controls
- 50-ft power cord for recovery unit
- 20-ft x 1/4" refrigerant hose
- Two 10-ft water hoses

Order Number	Voltage Options	Model
HPS-C-D24-3	220-480V,50/60Hz,3Ph,35A	Service Cart
HPS-P-D24-3	220-480V,50/60Hz,3Ph,35A	Permanent Mount

RefTec International, Inc.
 10530 Portal Crossing W, Suite 104
 Bradenton, FL 34211

Tel: 800-214-4883
 Sales fax: 941-750-0222
www.reftec.com
 email: sales@reftec.com