



Datos de Rendimiento de Herméticos Para Aire Acondicionado - **R-22 - 60 Hz - BTUH**

Modelo	Monofásico				Trifásico			
	BTUH	VATIOS DE MOTOR	PFJ/T/Z AMPERIOS	EER	BTUH	VATIOS DE MOTOR	TF5/D(M AMPERIOS	EER
HERMÉTICOS R-22								
CR16KQ	16,000	1,630	8.3	9.8				
CR16K6	16,300	1,540	6.9	10.6				
CR18KQ	18,300	1,870	8.3	9.8	18,000	1,810	5.6/2.8	9.9
CR18K6	18,000	1,700	7.6	10.6				
CR20KQ	19,800	1,980	8.9	10				
CR20K6	19,600	1,830	8.2	10.7				
CR22KQ	21,800	2,230	10.8	9.8				
CR22K6	22,100	2,040	9.2	10.8	21,600	1,990	6.0/3.0	10.9
CR24KQ	23,800	2,400	11.9	9.9	24,000	2,410	6.9/3.5	10
CR24K6	24,500	2,250	10	10.9	24,000	2,210	6.7/3.4	10.9
CR26K6	26,200	2,440	11.4	10.7				
CR28KQ	27,600	2,800	13.4	9.9	28,000	2,810	8.2/4.1	10
CR28K6	28,200	2,610	12.4	10.8	28,100	2,560	8.0/4.0	11
CR30KQ	29,800	2,990	14.2	9.9	30,000	3,010	--/4.3	10
CR30K6	30,000	2,750	12.9	10.9	29,800	2,710	8.3/4.2	11
CR32KQ	31,900	3,230	15.2	9.9	32,000	3,210	9.3/4.7	10
CR32K6	32,000	2,970	13.6	10.8	31,900	2,910	9.1/4.6	11
CR34K6	34,500	3,160	14.6	10.9				
CR34KQ	34,000	3,370	15.3	10.1	33,900	3,350	9.7/4.8	10.1
CR35K6	35,000	3,230	15.4	10.8	34,900	3,160	9.6/4.8	11
CR37KQ	36,800	3,640	17.4	10.1	36,400	3,500	10.2/5.1	10.4
CR38K6	38,200	3,520	17.2	10.9	37,900	3,440	10.5/5.3	11
CR41KQ	41,000	4,060	18.5	10.1	40,600	3,980	11.5/5.8	10.2
CR42K6	41,900	3,860	17.9	10.9	41,700	3,810	11.6/5.8	10.9
CR47KQ	47,500	4,580	21.5	10.4	47,200	4,540	13.7/6.9	10.4
CR53KQ	53,000	5,270	24	10.2	53,200	5,220	16.0/8.0	10.2
CR60K5	59,000	5,760	25.8	10.1	58,600	5,700	16.1/8.1	10.3
CRN5-0500	64,400	6,270	28	10	63,300	6,210	18.2/9.1	10.2

TEMPERATURA DE EVAPORACIÓN °F / °C	TEMPERATURA DE CONDENSACIÓN °F / °C	TEMPERATURA AMBIENTE °F / °C	TEMPERATURA DEL LÍQUIDO °F / °C	TEMPERATURA DEL GAS DE RETORNO °F / °C
45 / 7.2	130 / 54.4	95 / 35.0	115 / 46.11	65 / 18.3