

Especificaciones Mecánicas de Semiherméticos Para Aire Acondicionado - **R-22**

Modelo	50Hz m ³ /hr	Dimensiones Generales (mm)			Dimensiones Entre Centros de Montaje (mm)		Peso (kg)
		L	W	H	L	W	
MODELOS ENFRIADOS POR REFRIGERANTE R-22							
ERC*-0200	9.6	410	305	322	7/8	5/8	84
ERF*-0311	13.1	435	305	322	1 1/8	5/8	93
3RA*-0310	17.8	457	330	322	1 1/8	5/8	93
NRB2-0400	19.7	511	330	387	1 1/8	5/8	121
NRA2-0500	23.1	511	330	387	1 1/8	5/8	121
NRM1-0500	27.5	535	330	387	1 1/8	5/8	121
MRH4-0760	32.2	594	330	430	1 3/8	1 1/8	147
9RJ1-0765	38.8	653	383	445	1 3/8	1 1/8	166
9RC1-1015	45.7	675	383	445	1 3/8	1 1/8	180
9RS1-1505	60.2	698	383	445	1 5/8	1 1/8	190
4RA3-2000	101.3	625	472	422	1 5/8	1 1/8	206
4RH1-2500	85.4	671	481	454	2 1/8	1 1/8	217
4RJ2-3000	102	690	503	454	2 1/8	1 1/8	245
6RH1-3500	128.1	766	521	454	2 1/8	1 1/8	253
6RJ1-4000	153	766	549	530	2 1/8	1 1/8	279

